

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
18 November 2004 (18.11.2004)

PCT

(10) International Publication Number
WO 2004/100335 A1

(51) International Patent Classification⁷: **H02H 3/12, 5/12**

(21) International Application Number:
PCT/EP2004/004895

(22) International Filing Date: 6 May 2004 (06.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
BG2003A000032 9 May 2003 (09.05.2003) IT

(71) Applicant and

(72) Inventor: **IAQUINANGELO, Armando** [IT/IT]; Via
Brughiera, 15, I-20010 Cornaredo (MI) (IT).

(74) Agents: **GIAVARINI, Francesco**, et al.; Zanolli & Gi-
avarini Srl, Viale Bianca Maria, 35, I-20122 Milano (IT).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, GR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MY, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI,
SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:
— *of inventorship (Rule 4.17(iv)) for US only*

Published:
— *with international search report*

[Continued on next page]

(54) Title: **A DEVICE FOR THE MANAGEMENT OF ELECTRICAL SOCKETS**



(57) Abstract: Described herein is a device for the management of electrical socket connected to a branch of an a.c. electrical network for domestic or industrial use, capable of monitoring the presence/absence of a connected load, as well as possible conditions of overload and short circuit thereof; the device advantageously enables variation of the level of the a.c. voltage to the socket according to said conditions of applied load

WO 2004/100335 A1



— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.